

## CPXC 170-12


## Cyclic Lead Carbon battery (3500 cycles)

Dimensions (mm)

Standard terminal (mm)



No image available  
at this time



### Typical applications

- Electric vehicles
- Mobility scooters
- Electric wheelchairs
- AGV and warehouse equipment
- Medical equipment
- Solar energy
- Recreational vehicles
- Marine
- Camper and caravan

### Features

- Valve Regulated Lead Carbon (Pb-C)
- Maintenance free
- Absorbent Glass Mat Technology (AGM)
- Low self discharge
- Designed for extreme cyclic use
- Can be discharged or stored in any position without leakage
- Battery cannot be charged while upside down
- Produced under ISO 9001 & ISO 14001

### Restrictions

This battery is classified as **non spillable** and is therefore **not restricted** for transport under **ADR regulations** (road transport), **IMDG code** (sea transport) and **IATA regulations** (air transport).

Nominal voltage	12 V
Nominal capacity (1.70V/c, 25°C)	20Hr: 184.2 Ah
	10Hr: 175.0 Ah
	5Hr: 153.5 Ah
	1Hr: 104.3 Ah
Internal resistance	≤4.0mΩ (fully charged)
Maximum charge current	65 A
Maximum discharge current	2040 A (max. 5 sec)
Number of cycles	3500 (50% D.O.D.)
Float use / cyclic use	13.2 - 13.8V / 13.8 - 14.4V
Charge temperature range	-20°C ~ 40°C
Discharge temperature range	-20°C ~ 50°C
Standard terminal	Insert M8 (19 Nm torque)
Housing material	ABS (UL94-HB)
Dimensions Length	520 mm
Dimensions Width	239 mm
Dimensions Height	225 mm
Approximate Weight	63.00 kg
Packing	1 pcs / box

### Recommended


Having the right battery is often just the beginning. Optimal use of a battery requires having a good battery charger, so that the user can be sure that their battery is always optimally charged and has maximum lifespan.

Cellpower offers various intelligent battery chargers, as well as battery testers, battery monitors and battery guards. All designed to easily monitor the battery quality and make sure the battery remains in the best condition possible.




Recommended for CPXC 170-12


## Charge characteristics




## Capacity in relation to temperature



## Charging time relation to D.O.D.



## Cycle service life in relation to depth of discharge



## Models available

Model	Voltage	Capacity (Ah)	Dimensions (mm)	Weight (kg)
CPXC 500-2	2	500	167x205x470/493	41.0
CPXC 1000-2	2	1000	192x209x645/668	70.0
CPXC 65-12	12	65	261x167x213	24.5
CPXC 80-12	12	80	331x171x221	30.5
CPXC 100-12	12	100	409x170x223	35.5
CPXC 120-12	12	120	481x169x239	41.0
CPXC 150-12	12	150	533x206x219	55.0
CPXC 170-12	12	170	523x238x224	63.0
CPXC 200-12	12	200	521x267x224	72.5

## Cellpower family

Cellpower supplies a broad range of reliable AGM, GEL and Lithium batteries. Each product series has its own unique characteristics, so that there is a suitable battery for every application with its associated specific usage profile. Combined with the right Cellpower battery accessories, you are able to assemble a high-quality and reliable battery system.

The sealed, maintenance-free AGM lead battery type has a long operational lifetime. When used correctly, the Absorbent Glass Mat (AGM) technology offers dependable, lasting service. Additionally, AGM batteries exhibit very little self-discharge when compared with other lead-acid batteries. Sealed lead-acid batteries require low maintenance and do not need to be refilled with water or other liquids.

