

# FLEX28048A



Input: 115 - 230 Vac

Output: 48 Vdc 60°C

Efficiency up to 91%

Strong overload without switch-off, up to 50%

Flexible Power continuity : from 240 to 345 W

Tree type of modality protections:

- 1) Hiccup mode
- 2) Continuous Out Mode
- 3) Manual Reset

DIN Rail Mountable

Extremely small size

3 Year warranty

## Features

### Input Data

Nominal Input Voltage (2 x Vac)	<b>115 – 230 Vac</b>
Manual select Input from 115 to 230	<b>90 – 135 (115)</b>
Input Voltage range (Vac)	<b>180 – 264 (230)</b>
Inrush Current (Vn and In Load) I <sup>2</sup> t	<b>≤ 16 A ≤ 5 msec.</b>
Frequency	<b>47 – 63 Hz ±6%</b>
Input Current (115 – 230 Vac)	<b>3.3 – 2.2 A</b>
Internal Fuse	<b>T 6.3 A</b>
External Fuse (recommended)	<b>16 A (curve B)</b>

### Output Data

Output Voltage (Vn) Factory Setting ±3%	<b>48 Vdc</b>
Adjustment range (Vadj)	<b>41 – 55 Vdc</b>
Start up with Strong Load (capacitive load)	<b>≤50.000µF</b>
Turn-On delay after applying mains voltage	<b>1 sec. (max)</b>
Rated Current at 48 V 40°C (In)	<b>7 A (permanent)</b>
Rated Current at 48 V 50°C (In)	<b>6 A (permanent)</b>
Rated Current at 48 V 60°C (In)	<b>5 A (permanent)</b>
Power Boost Current at 48 Vdc 60°C(In)	<b>In 60°C x 1.5 ≥ 3 min.</b>
Current max. Overload ≅ 4Vdc (permanent)	<b>I<sub>max</sub>=In60°Cx(1.8 -2.2)</b>
Current Short Circuit I <sub>cc</sub>	
Max 2 sec.: Hiccup mode	<b>In 60°C x 3</b>
Permanent : Continuous Mode	
Hold-up Time ( min. Vac) 48Vdc 5A	<b>Typ. 20 msec</b>
Residual Ripple	<b>≤ 80 mV<sub>pp</sub></b>
Efficiency	<b>≥ 91 %</b>
Over temperature Protection	<b>Yes. Shut-down output and automatic restart.</b>
Short-circuit protection	<b>1° Hiccup Mode</b>
	<b>2° Continuous Out Mode</b>
	<b>3° Manual Reset</b>
Dissipation power load max (W)	<b>28</b>
Over Load protection	<b>Yes</b>
Over Voltage Output protection	<b>Yes (typ. 72 Vdc)</b>
Parallel connection	<b>Yes "Easy Parallel"</b>

### Climatic Data

Ambient Temperature operation	<b>-25 up to +70 °C</b> <b>(&gt;-60°derating 2.5% °C)</b>
Ambient Temperature Storage	<b>-40 up to +85 °C</b>
Humidity at 25 °C, no condensation	<b>95 % to 25 °C</b>

### General Data

Isolation Voltage (In / Out)	<b>3000 Vac</b>
Isolation Voltage (In / PE)	<b>1605 Vac</b>
Isolation Voltage (Out / PE)	<b>500 Vac</b>
Protection Class (EN/IEC 60529)	<b>IP 20</b>
Reliability: MTBF IEC 61709	<b>&gt; 500.000 h</b>
Pollution Degree Environment	<b>2</b>
Connection Terminal Blocks Screw Type	<b>2,5 mm</b>
Protection class	<b>I with PE connected</b>
Dimension (w-h-d)	<b>72x115x135 mm</b>
Weight	<b>0.77 kg approx.</b>

## Norms and certifications

The CE mark in According to EMC 2004/108/EC and Low voltage directive 2006/95/EC.

### Electrical Safety

In compliance to UL508.

According to IEC/EN 60950 (VDE 0805) e EN 50178 (VDE 0160) for assembling device. The unit must be installed according to IEC/EN 60950. Input / Output separation: SELV EN60950-1 and PELV EN 60204-1. Double or reinforced insulation.

### EMC Immunity

EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN61000-6-2

### EMC Emission:

EN61000-6-4

### Standards Conformity

EN 60204-1 Safety of Electrical Equipment Machines

